NSAI	Document Ref.:	AD-AC-0635
	Revision:	1.0
Plating record for 46t GCW/GTW Vehicle Combinations. Form PV3	Date issued:	2026-05-29
	Page:	**1** of **1**

Completed PV3 form to be posted to: Data Services, Driver and Vehicle Computer Division (DVCSD), Shannon Town Centre, Shannon, Co. Clare. Tel: (061) 365000/Locall 1890 411412

Vehicle owner: .....
Address: .....
.....
Description of vehicle (as per Plating Guidelines) .....
Vehicle Registration Number: .....

Vehicle Identification Number: | | | | | | | | | | | | | | | | | | |

Rigid ☐ Tractor Unit ☐ *(please tick appropriate box)*

Copy of Declaration of Conformity (DOC) Attached:	**Yes:**	**No:**	**Copy of fully completed DOC must be attached to this record.**

Condition	**Yes**	**No**	**Remark**
Vehicle VIN matches VIN recorded on DOC:			**Not possible to plate vehicle with GCW of 40(46)t if there is a "No" recorded for any condition.**
Design Gross Combination Weight (GCW) 46t or greater:			
Number of axles *(3 axles minimum required):*			

Name of Manufacturer:						
Type Approval Number (if available):						
			Weights not to be exceeded in the State (IE)	Maximum authorised weights (EU)	Technically Permissible Weight	Axle Group (if applicable)
Maximum permitted laden weight (**kg**):						
Maximum permitted laden weight of combination [40(46)t for Ireland, 40(44)t for **tractor unit** Europe, 40t for **rigid** Europe]						
Axle weights (kg)	Load Index	Single or Twin **S/T**				
1						
2						
3						
4						
Vehicle Length (m):	**L =**				**(to 2 decimal places)**	
Vehicle Width (m):	**W =**				**(to 2 decimal places)**	
Is vehicle fitted with coupling?				Yes	No	
Is coupling adjustable?				Yes	No	
Data relating to length of combination. Centre of coupling to front of vehicle:		Adjustable	amax (m):		amin (m)	
		Non-adjustable	a (m)			

Rigid 3 axle spacing X:	m	Max weight is 25t. Subject to 5.5t per metre of axle spacing X*****
Rigid 4 axle spacing X:	m	Max weight is 30t. Subject to 5t per metre of axle spacing X**
Tractor unit 3 axle spacing X:	m	Max weight is 25t. Subject to 6t per metre of axle spacing X*****
Tandem axle spacing:	m	Between 1.3m and 1.8m, max. weight is 19t.
Number of driving axles:		
Each driving axle fitted with twin tyres and air suspension system:		Yes: ☐ No: ☐ ***If "No" vehicle cannot be plated with 40(46)t GCW***

***26t when fitted with twin tyres and road friendly suspension on each driving axle.**
****32t when fitted with twin tyres and road friendly suspension on each driving axle.**

Approved Workshop: **Appointed person:**

Date: **Signature:**

Swift Square, Northwood, Santry, Dublin 9. Tel: (01) 807 3800. Fax. (01) 807 3844