

Plating of vehicles – Workshop Record – Plating of Mechanically Propelled vehicle. Form PV1.

 Vehicle owner:.....
 Address:.....

 Description of vehicle (as per Plating Guidelines):

Vehicle Registration Number:.....

 Vehicle Identification Number:

 Rigid Tractor Unit Bus (please tick appropriate box)

Name of Manufacturer:			
Type Approval Number (if available):			
Vehicle equipped to tow a trailer:		Yes:	No:
		Weights not to be exceeded in Ireland.	Max. weights permitted under EU Directives
Maximum permitted laden weight (kgs):			Design weights (if higher than permitted in Ireland)
Maximum permitted laden weight of combination (if permitted to tow a trailer) (kgs):			
2 axle MP vehicle axle spacing:		If < 3m, max. weight is 16t. If > 3m, max. weight is 18t. Max weight for two axle buses is 19.5t	
3 axle MP vehicle axle spacing X:		Max weight is 25t. Subject to 5.5t per metre of axle spacing X*	
4 axle MP vehicle axle spacing X:		Max weight is 30t. Subject to 5t per metre of axle spacing X**	
Tandem axle spacing one or both axles driven:		Between 1.3m and 1.8m, max. weight is 19t.	
2 axle tractor unit axle spacing:		If < 3m max. weight is 16t. If > 3m max. weight is 18t.	
3 axle tractor unit axle spacing X:		Max weight is 25t. Subject to 6t per metre of axle spacing X.*	
4 axle tractor unit axle spacing X:		Max weight is 30t. Subject to 6t per metre of axle spacing X.	
2 axle tractor unit, GCW 40t		2 axle MP vehicle equipped to tow a trailer – GTW is 36t. 3 axle MP vehicle equipped to tow a trailer – GTW is 40t. 4 axle, MP, 1 drive axle, twin tyres, air suspension, 32t** 4 axle MP, 2 drive axles, twin tyres, 30(32)t**	
3, 4 axle tractor unit, GCW 40 (44)t.			
3 axle articulated bus, max. 28t.			
Tandem axle spacing, no axles driven:		Less than 1.0m, max. weight is 11.5t. Between 1.0m and 1.3m, max. weight is 16t. Between 1.3m and 1.8m, max. weight is 18t.	
		Load Index (Not Tyre Size)	Single or Twin S/T.
Axle weights (kgs)	Axle 1:		
	Axle 2:		
	Axle 3:		
	Axle 4:		
Vehicle Length (m):	L =		
Vehicle Width (m):	W =		
Is vehicle fitted with fifth wheel coupling?		Yes:	No:
Is fifth wheel coupling adjustable?		Yes:	No:
Data relating to length of combination. Centre of coupling to front of vehicle:		Adjustable:	amax (m):
		Non-adjustable:	a (m):

*26t when fitted with twin tyres and road friendly suspension on each driving axle.

Approved Workshop:

Appointed person:

Date:

Signature: