



Vehicle owner:

Address:

.....

Description of trailer/semi-trailer (as per Plating Guidelines):

Vehicle Registration Number:

Vehicle Identification Number:

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Rigid Tractor Unit Bus (please tick appropriate box)

Name of Manufacturer:				
Type Approval Number (if available):				
		Weights not to be exceeded in Ireland	Max. weights permitted under EU Directives	Design weights (if higher than permitted in Ireland)
Maximum permitted laden weight (trailers only, not applicable to semi-trailers) (kgs):				
Tandem axle spacing (m):		Less than 1.0m, max. weight transmitted is 11.5t. Between 1.0 and 1.3m, max. weight transmitted is 16t. Between 1.3 and 1.8m, max. weight transmitted is 18t. Greater than 1.8m, max. weight transmitted is 20t.		
Triaxle spacing (m):		Less than 1.3m, max. weight transmitted is 21t. Greater than 1.3m, max. weight transmitted is 24t.		
4 axle bogie spacings (m):		Max weight is 24t.		
		Load Index (Not Tyre Size)	Single or Twin S/T.	
Axle Weights (kgs)	Axle 1:			
	Axle 2:			
	Axle 3:			
	Axle 4:			
Trailer/semi-trailer Length (m):	L = (to 2 decimal places)			
Trailer/semi-trailer Width (m):	W = (to 2 decimal places)			
Maximum king-pin load (kgs): If not available, then semi-trailer cannot be plated.				
Is King-Pin adjustable?		Yes:	No:	
Data relating to length of combination. Centre of king-pin to rear of semi-trailer:		Adjustable:	bmax (m):	bmin (m):
		Non-adjustable:	b (m):	

Approved Workshop:

Appointed person:

Date:

Signature: